


## NA49...2RS Series



RNA 49..2RS

| select     | Inquiry | Bearing No. | Boundary dimensions mm |       |    |       |       | Basic load ratings(kN) |             | Limiting speed(rpm Mass )<br>Oil Kg |
|------------|---------|-------------|------------------------|-------|----|-------|-------|------------------------|-------------|-------------------------------------|
|            |         |             | d                      | Fw(F) | D  | C     | B     | Dynamic(Cr)            | Static(Cor) |                                     |
| NA4900-2RS | 10      | 14          | 22                     | 13    | 14 | 4560  | 4660  | 13000                  | 24.5        |                                     |
| NA4901-2RS | 12      | 16          | 24                     | 13    | 14 | 5980  | 9500  | 12000                  | 27.5        |                                     |
| NA4902-2RS | 15      | 20          | 28                     | 13    | 14 | 5980  | 9500  | 10000                  | 37          |                                     |
| NA4903-2RS | 17      | 22          | 30                     | 13    | 14 | 6050  | 10100 | 9000                   | 40          |                                     |
| NA4904-2RS | 20      | 25          | 37                     | 17    | 18 | 14900 | 17500 | 7500                   | 80          |                                     |
| NA4905-2RS | 25      | 30          | 42                     | 17    | 18 | 16300 | 21500 | 6500                   | 89.5        |                                     |
| NA4906-2RS | 30      | 35          | 47                     | 17    | 18 | 20050 | 24900 | 5500                   | 104         |                                     |
| NA4907-2RS | 35      | 42          | 55                     | 20    | 21 | 22500 | 37000 | 4800                   | 175         |                                     |
| NA4908-2RS | 40      | 48          | 62                     | 22    | 23 | 33050 | 50900 | 4200                   | 252         |                                     |
| NA4909-2RS | 45      | 52          | 68                     | 22    | 23 | 34800 | 56800 | 3900                   | 290         |                                     |
| NA4910-2RS | 50      | 58          | 72                     | 22    | 23 | 37800 | 61500 | 3500                   | 295         |                                     |