


Metric Series



select	Inquiry	Bearing NO.	Dimension(mm)								Basic Load Rating(N)		Limited speed rpm	Weight (kg)	
			d(mm)	D(mm)	D1	D2	B(mm)	B1	C1	C2	r min(mm)	Dynamic(Cr)			Static(Cor)
F681	1	3	3.8	-	1	-	0.3	-	0.05	80	23		150000	0.04	
F691	1	4	5	-	1.6	-	0.5	-	0.1	140	36		120000	0.14	
MF41 X	1.2	4	4.8	-	1.8	-	0.4	-	0.1	138	35		130000	0.12	
F681XF	1.5	4	5	5	1.2	2	0.4	0.6	0.15	112	33	100000	120000	0.09	
F691XF	1.5	5	6.5	6.5	2	2.6	0.6	0.8	0.15	237	69	85000	100000	0.23	
F601XF	1.5	6	7.5	7.5	2.5	3	0.6	0.8	0.15	330	98	75000	90000	0.42	
F682	2	5	6.1	6.1	1.5	2.3	0.5	0.6	0.08	169	50	85000	100000	0.16	
MF52 B	2	5	6.2	6.2	2	2.5	0.6	0.6	0.1	187	58	85000	100000	0.21	
F692	2	6	7.5	7.5	2.3	3	0.6	0.8	0.15	330	98	75000	90000	0.35	
MF62	2	6	7.2	-	2.5	-	0.6	-	0.15	330	98		90000	0.36	
MF72	2	7	8.2	8.2	2.5	3	0.6	0.6	0.15	385	127	63000	75000	0.52	
MF602	2	7	8.5	8.5	2.8	3.5	0.7	0.9	0.15	385	127	63000	75000	0.6	
F682XF	2.5	6	7.1	7.1	1.8	2.6	0.5	0.8	0.08	208	74	71000	80000	0.25	
F692XF	2.5	7	8.5	8.5	2.5	3.5	0.7	0.9	0.15	385	127	63000	75000	0.51	
MF82X	2.5	8	9.2	-	2.5	-	0.6	-	0.2	560	179		67000	0.62	
F602XF	2.5	8	9.5	9.5	2.8	4	0.7	0.9	0.15	550	175	60000	71000	0.74	
MF63	3	6	7.2	7.2	2	2.5	0.6	0.6	0.1	208	74	71000	80000	0.27	
F683A	3	7	8.1	8.1	2	3	0.5	0.8	0.1	390	130	63000	75000	0.37	
MF83	3	8	9.2	9.2	2.5	3	0.6	-	0.15	560	179	60000	67000	0.56	
F693	3	8	9.5	9.5	3	4	0.7	0.9	0.15	560	179	60000	67000	0.7	
MF93	3	9	10.2	10.6	2.5	4	0.6	0.8	0.2	570	187	56000	67000	0.81	
F603	3	9	10.5	10.5	3	5	0.7	1	0.15	570	187	56000	67000	1	
F623	3	10	11.5	11.5	4	4	1	1	0.15	630	218	50000	60000	1.85	
F633	3	13	15	15	5	5	1	1	0.2	1300	485	36000	43000	3.73	
MF74	4	7	8.2	8.2	2	2.5	0.6	0.6	0.1	310	115	60000	67000	0.29	
MF84		8	9.2	9.2	2	3	0.6	0.6	0.15	395	139	56000	67000	0.44	
F684		9	10.3	10.3	2.5	4	0.6	1	0.15	640	225	53000	63000	0.7	
MF104B		10	11.2	11.6	3	4	0.6	0.8	0.2	710	270	50000	60000	1.13	
F694		11	12.5	12.5	4	4	1	1	0.15	960	345	48000	56000	1.91	
F604		12	13.5	13.5	4	4	1	1	0.2	960	345	48000	56000	2.53	