

SAPP Series - Eccentric Locking Collar Type



select	Inquiry	Unit No.	Shaft Diameter d	Shaft Height H (in)	Mounting Hole Center-to-Center J (in)	Housing Length L (in)	Housing Width A (in)	Basic Dynamic Load Rating (Cr) lbs	Basic Static Load Rating (Cor) lbs
SAPP201-12MM	12 mm	0.875	2.6772	3.3858	0.9843	2158.17	1034.12		
SAPP201-8	1/2 in	0.875	2.6772	3.3858	0.9843	2158.17	1034.12		
SAPP202-10	5/8 in	0.875	2.6772	3.3858	0.9843	2158.17	1034.12		
SAPP202-15MM	15 mm	0.875	2.6772	3.3858	0.9843	2158.17	1034.12		
SAPP203-11	11/16 in	0.875	2.6772	3.3858	0.9843	2158.17	1034.12		
SAPP203-17MM	17 mm	0.875	2.6772	3.3858	0.9843	2158.17	1034.12		
SAPP204-12	3/4 in	1	2.9921	3.8583	1.2598	2877.55	1494.98		
SAPP204-20MM	20 mm	1	2.9921	3.8583	1.2598	2877.55	1494.98		
SAPP205-14	7/8 in	1.125	3.3858	4.252	1.2598	3147.33	1764.75		
SAPP205-15	15/16 in	1.125	3.3858	4.252	1.2598	3147.33	1764.75		
SAPP205-16	1 in	1.125	3.3858	4.252	1.2598	3147.33	1764.75		
SAPP205-25MM	25 mm	1.125	3.3858	4.252	1.2598	3147.33	1764.75		
SAPP206-18	1-1/8 in	1.3125	3.7402	4.6063	1.4961	4383.77	2540.34		
SAPP206-19	1-3/16 in	1.3125	3.7402	4.6063	1.4961	4383.77	2540.34		
SAPP206-20	1-1/4 in	1.3125	3.7402	4.6063	1.4961	4383.77	2540.34		
SAPP206-30MM	30 mm	1.3125	3.7402	4.6063	1.4961	4383.77	2540.34		

SAPP Series - Eccentric Locking Collar Type

SAPP206-30MM	30 mm	1.3125	3.7402	4.6063	1.4961	4383.77	2540.34
SAPP207-20	1-1/4 in	1.5625	4.1732	5.0787	1.6535	5777.59	3439.58
SAPP207-21	1-5/16 in	1.5625	4.1732	5.0787	1.6535	5777.59	3439.58
SAPP207-22	1-3/8 in	1.5625	4.1732	5.0787	1.6535	5777.59	3439.58
SAPP207-23	1-7/16 in	1.5625	4.1732	5.0787	1.6535	5777.59	3439.58
SAPP207-35MM	35 mm	1.5625	4.1732	5.0787	1.6535	5777.59	3439.58